

CSP-D00388 Mic. screw lock short stem silver

DICENTIS



- ▶ Unidirectional microphone on adjustable stem
- ▶ Built-in plop and windshield
- ▶ Low susceptibility to mobile phones
- ▶ For acoustical challenging rooms

The innovative, stylish and ergonomically designed microphone with adjustable stem has a unidirectional response for optimum performance, even in noisy conditions or acoustical challenging rooms. It has low susceptibility to interference from mobile phones.

Functions

Controls and indicators

- Red and green illuminator. Red indicates microphone active, green indicates request for speech accepted.

Interconnections

- Connector to plug and fasten the microphone.

Parts included

| Quantity | Component |
|----------|----------------------------------------------|
| 1 | CSP-D00388 Mic. screw lock short stem silver |

Technical specifications

Electrical

| | |
|---------------------------------------|-----------------|
| Power supply (VDC) | 5 VDC |
| Power consumption (W) | 0.10 W |
| Bandwidth (Hz) | 125 Hz – 15 kHz |
| Dynamic range (dB) | 100 dB |
| Nominal acoustic input level (dB SPL) | 85 dB SPL |

| | |
|---------------------------------------|------------|
| Maximum acoustic input level (dB SPL) | 115 dB SPL |
| Self noise (dB SPL) | 15 dB SPL |

Mechanical

| | |
|-------------------------------------|---------------------------|
| Microphone stem length (mm) | 310 mm |
| Microphone stem length (in) | 12.21 in |
| Dimensions (Ø x H) (mm) (connector) | 0.63 mm x 1.63 mm |
| Dimensions (Ø x H) (in) (connector) | 15.9 in x 41.3 in |
| Weight (g) | 91 g |
| Weight (lb) | 0.20 lb |
| Color in RAL | RAL 9022 Pearl light gray |

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

| | |
|---------------------------------|-----------------|
| Operating temperature (°C) | 5 °C – 45 °C |
| Operating temperature (°F) | 41 °F – 113 °F |
| Transportation temperature (°C) | -30 °C – 70 °C |
| Transportation temperature (°F) | -22 °F – 158 °F |
| Storage temperature (°C) | 5 °C – 45 °C |

| | |
|-------------------------------------------------|----------------|
| Storage temperature (°F) | 23 °F – 113 °F |
| Operating relative humidity, non-condensing (%) | 5% – 90% |

Ordering information

CSP-D00388 Mic. screw lock short stem silver
Screw locked microphone with short stem for the
DICENTIS Conference system.
Order number **CSP-D00388 | F.01U.412.151**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com